

THE INDIUM CORPORATION OF AMERICA®

QUOTATION

Customer: 63000

Johnny Green
Fermi Lab
Kirk Rd. & E. Wilson St.
Attn: Receiving Dept
Batavia IL 60510
USA

Phone: 630-840-3392

Page: 1

ICA Contact: Lisa Clark

Customer RFQ #:

Quote Date: 04/03/12

Expiration Date: 05/03/12

Terms: N/30 of Invoice

Delivery Terms: FCA

Clinton NY

Customer Currency: US\$ US Dollar

ICA Territory: illinois

ICA Estimate: E009092

*** Effective 01 Jan 2011: Shipping terms based on Incoterms 2010®, unless otherwise stated. ***

<u>Item / Description</u>	<u>Quantity</u>	<u>UM</u>	<u>Unit Price</u>	<u>Net Amount</u>
PASTEOT-800515-ULA	500.000		4.50000	2,250.00
SAC305 8.9E TYPE 4 88.5% ULA Sensitive		GM		

Pack: 500gm/jar

Lead time: 10-12 weeks after receipt of order

Single release

Sale Amount: 2,250.00

USA Tax: 0.00

GST/VAT: 0.00

Misc: 0.00

Total Amount: 2,250.00

Please contact us immediately to discuss any issues with this correspondence.
Thank you for your business.

INDIUM

THE INDIUM CORPORATION OF AMERICA®

www.indium.com
askus@indium.com
PRC +86 (0)512 628 34900
SINGAPORE +65 6 268 8678
UK +44 (0) 1908 580400
USA +1 315 853 4900



ISO 9001
REGISTERED

Y002-007.RVF 10 FEB 2011



**INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®
INDIUM CORPORATION (SUZHOU)®
SAFETY DATA SHEET**

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH INDIUM3.2 FLUX VEHICLE

MSDS Number: MSDS- 4145

Revised Date: 6 JUNE 2011

Product Use: Industrial Use - Water wash solder paste consisting of a flux vehicle blended with an 83-92 % pre-alloyed metal powder. (mixture)

MANUFACTURER:

In America:

The Indium Corporation of America
1676 Lincoln Ave., Utica NY 13502
Information: (315) 853-4900
nswarts@indium.com

EMERGENCY PHONE:

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887

In Europe:

Indium Corporation of Europe
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou), Co. Ltd.
No. 428 Xinglong Street
Suzhou Industrial Park
Suchun Industrial Square
Unit No. 14-C
Jiangsu Province, China 215126
Information: (86) 512-6283-4900

In Asia:

Asia-Pacific Operations-Singapore
29 Kian Teck Avenue
Singapore 628908
Information: +65 6268-8678

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

⊗ Eye ⊗ Inhalation ⊗ Skin ⊗ Ingestion NTP

Carcinogen listed in

IARC OSHA ⊗Not Listed
*See Section 11

GHS:



lead and/or antimony

Signal Word: Warning

Hazard statement(s)

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer (lead) (proprietary ingredient 0.2%)
H360	May damage fertility or the unborn child (applicable to lead containing product)
H373	May cause damage to organs through prolonged or repeated exposure (applicable to lead containing product)
H400+H413	Very toxic to aquatic life, may cause long lasting harmful effects to aquatic life (lead) (antimony)
EUH201A	Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.

Precautionary statement(s)

P233	Keep container tightly closed
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362	Take off contaminated clothing and wash before reuse
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P304 + 341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes

POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause serious eye irritation.

Ingestion: This product contains metal alloy powder and organic chemicals. Harmful if swallowed.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to mucous membranes and the upper respiratory tract.

Skin Contact: May cause skin irritation. Contact with **Antimony** may cause irritation or dermatitis.

Chronic: **TIN:** Has been shown to increase incidence of sarcoma in animal tests.

SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.

INDIUM: May cause damage to respiratory system. Kidney and liver damage from injection of indium compounds has been reported based on limited animal testing. Target organs: teeth and gums

BISMUTH: May cause kidney damage.

Warning: This product contains chemical (s) known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (Includes trace levels of ethylene oxide, acetaldehyde 1, 4 dioxane and lead)

Note: The Indium Corporation does not recommend, manufacture, market or endorse any of it's products for human consumption.

Warning: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making joints or fittings in any private or public water supply system. Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
TIN	*	7440-31-5 (US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-
SILVER	*	7440-22-4 (US)	0.01	0.01	N.E.
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Mexico)	-	0.1	-
		(Singapore)	0.1	-	-
COPPER	*	7440-50-8 (US)	0.1	0.2	-
		(EU)	-	0.2	2
		(Canada)	-	0.2	0.6
		(Singapore)	0.2	1(dust)	-
		(Mexico)	-	0.2	2
		(China)	-	0.2(fume)	0.6
			-	1(dust)	2.5
ANTIMONY	*	7440-36-0 (US)	0.5	0.5	-
		(EU)	0.5	-	-
		(Canada)	-	0.5	1.5
		(Mexico)	N.E.	0.5	-
		(Singapore)	0.5	-	-

		(China)	-	0.5	-
BISMUTH	*	7440-69-9	N.E.	N.E.	N.E.
INDIUM	*	7440-74-6/231-180-0			
		(US)	0.1	0.1	-
		(EU)	-	0.1	0.3
		(Canada)	-	0.1	0.3
		(Singapore)	0.1	-	-
		(Mexico)	0.1	-	0.3
		(China)	0.1	-	0.3
GOLD	*	7440-57-5	N.E.	N.E.	N.E.
LEAD	*	7439-92-1 (US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Canada)	-	0.05	-
		(Singapore)	0.15	-	-
		(Mexico)	-	0.15	-
		(China)	-	0.05(dust)	-
			-	0.03(fume)	-
PROPRIETARY ACTIVATOR	3.4-6.7		N.E.	N.E.	N.E.
PROPRIETARY AMINE	1.6-3.3	(US)	N.E.	5	N.E.
		(Singapore)	5	-	-
POLYGLYCOL ETHER	3.0-7.0	9038-95-3	N.E.	N.E.	N.E.

DOES NOT CONTAIN ANY LISTED EU REACH SUBSTANCES OF VERY HIGH CONCERN (SVHC)

* See alloy table at end of document

Symbol: Xn

Risk Phrases: R20/21/22,R36/37/38, See Section 15 for additional information

N.E. = Not established

EU = European Union Occupational Exposure Limits

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. **Method:** Not established.
Auto-ignition Temperature: Not established.
Flammable Limits: Limits not established.
Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.
Special Fire Fighting Procedures: Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations. Wear proper personal protective equipment during clean up.

7. HANDLING AND STORAGE

Handling Precautions: Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. Do not touch or rub eyes until hands are washed.
Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use only with production equipment (stencil printers and re-flow furnaces) with adequate ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components so that they're permissible exposure levels are not exceeded.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.
Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.
Skin: Compatible chemical resistant gloves.
Other: Lab coat, eyewash fountain in work area. Avoid the use of contact lenses in high fume areas.
Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately. Do not allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Grey colored paste.	Boiling Point:	Not applicable.
Odor:	Mild characteristic odor.	Melting Point:	Not applicable
Specific Gravity:	Not applicable.	pH:	Not applicable
Vapor Pressure:	Not applicable.	Solubility in Water:	Soluble
Vapor Density:	(air=1) Not applicable.		

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Not established.
Incompatible Materials:	Avoid contact with acids, bases or oxidizing agents.
Hazardous Decomposition /	Harmful toxic oxide fumes may form at elevated temperatures. CO/CO ₂ /HBr
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	NTP: No	
	OSHA: No	29CFR1910.1025
	IARC: Yes	Lead and lead compounds are listed as possible carcinogens.
	Other:	Lead can cause potential harm to the developing fetus.

Lead – Suspected human reproductive toxicant. May cause damage to organs through prolonged or repeated exposure.
Reproductive toxicity – rat –inhalation, oral/ effects on newborn.

12. ECOLOGICAL INFORMATION

This section is subject to future development.

Product not tested.

Lead – Toxicity to fish – mortality LOEC – rainbow trout – 1.19 mg/l – 96h. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Bioaccumulation – Oncorhynchus kisutch – 2 weeks
Bioconcentration factor (BCF): 12. Fresh fish: 0.44 mg/l LC50 96h/ 1.32 mg/l LC50 96h/water Flea: 600 ug/l EC50 = 48h

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated (Department of Transportation).

Non hazardous under shipping regulations.

UN - none

15. REGULATORY INFORMATION

The information in this Material Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS:

D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic) (lead)



This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

California PROP 65: WARNING:

This product contains chemical (s) known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (Includes lead and trace levels of ethylene oxide, acetaldehyde and 1, 4 dioxane)

SARA 313 Listing - 40 CFR 372.65

Ethylene Oxide CAS# 75-21-8

Silver CAS# 7440-22-4

Lead CAS# 7439-92-1

1, 4 Dioxane CAS# 123-91-1

Copper CAS# 7440-50-8

Acetaldehyde CAS# 75-07-0

Antimony CAS# 7440-36-0

All ingredients in this product are listed on the EPA TSCA Inventory.

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

X_n

Risk Phrases:

- R20/21/22 Harmful by inhalation, in contact with skin and if swallowed (lead)
R36/37/38 Irritating to eyes, respiratory system and skin
R33 Danger of cumulative effects (lead)
R61 May cause harm to the unborn child (lead)
R40 Limited evidence of carcinogenic effect (lead)
R48 Danger of serious damage to health by prolonged exposure (lead)
R52/53 Harmful to aquatic organisms and may cause long-term effects in the aquatic environment

Safety Phrases:

- S20/21 When using do not eat, drink or smoke
S23 Do not breathe fumes
S24/25 Avoid contact with skin and eyes
S28 After contact with skin wash immediately with plenty of soap and water
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection
S62 If swallowed, do not induce vomiting seek medical advice immediately and show container or label
S7 Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating:

Health:	2
Fire:	1
Reactivity:	0

Revised Date: 6 JUNE 2011

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Note: This MSDS may be translated into an international language. If there is any misinterpretation or misunderstanding of any words or phrases that may occur within any translation the ENGLISH language shall always prevail.

ALLOY TABLE**Metal alloy mix with flux**

INDALLOY	%TIN Sn	%SILVER Ag	%ANTIMONY Sb	%COPPER Cu	% INDIUM In	%BISMUTH Bi	%LEAD Pb	%GOLD Au	RoHS* Compliance
106 (Sn63/Pb37)	52.3-58	-	-	-	-	-	-	-	NO
121 (Sn96.5/Ag3.5)	80-88.8	2.9-3.2	-	-	-	-	-	-	YES
128 (100Sn)	83-92	-	-	-	-	-	-	-	YES
133 (Sn95/Sb5)	78.9- 87.4	-	4.2-4.6	-	-	-	-	-	YES
182 (Au80/Sn20)	16.6- 18.4	-	-	-	-	-	-	66.4- 73.6	YES
209 (Sn65/Ag25/Sb10)	54-59.8	20.8-23.0	8.3-9.2	-	-	-	-	-	YES
241 (SAC387) (Sn95.5/Ag3.8/Cu0.7)	79.3- 87.9	3.2-3.5	-	0.58-0.64	-	-	-	-	YES
244 (99.3Sn/0.7Cu)	82.4 - 91.3	-	-	0.58 – 0.64	-	-	-	-	YES
246 (Sn95.5/Ag4/Cu0.5)	79.3- 87.9	3.3-3.7	-	0.42-0.46	-	-	-	-	YES
249 (Sn91.8/Bi4.8/Ag3.4)	76.2- 84.5	2.8-3.1	-	-	-	4.0-4.4	-	-	YES
252 (Sn95.5/Ag3.9/Cu0.6)	79.3- 87.9	3.2-3.6	-	0.50-0.55	-	-	-	-	YES
254 (86.9Sn/10In/3.1Ag)	72-80	2.6-2.9	-	-	8.3-9.2	-	-	-	YES
256 (SAC 305) (Sn96.5/Ag3.0/Cu0.5)	80.1- 88.8	2.5-2.8	-	0.42-0.46	-	-	-	-	YES
258 (Sn98.5/Ag1/Cu 0.5)	81.8- 90.6	0.83-0.92	-	0.42-0.46	-	-	-	-	YES
259 (Sn90/Sb10)	74.7- 82.8	-	8.3-9.2	-	-	-	-	-	YES
282 (Bi57/Sn42/Ag1)	34.9- 38.6	0.83-0.92	-	-	-	47.3-52.4	-	-	YES
Non Standard (Sn96/Ag4)	79.7- 88.3	3.3-3.7	-	-	-	-	-	-	YES

***RoHS = Restriction of Hazardous Substances EU Directive 2002/95/EC Solder related products are not directly related to the regulations. It is the customer's responsibility to ensure compliance. Review any applicable exemptions that may apply.**

<http://www.pbfree.com>

http://europa.eu.int/comm/environment/waste/weee_index.tm